

40288/DWR/D453

This cover or fee is being deposited with the  
United States Postal Service "Express Mail  
Post Office to Addressee" under 37 CFR § 1.10  
Mailing Label No. EL386899704US

**SYSTEM AND METHOD FOR ASSEMBLING DISCRETE DATA FILES INTO AN  
EXECUTABLE FILE AND FOR PROCESSING THE EXECUTABLE FILE**

**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application contains subject matter than may be considered related to the subject matter disclosed in U.S. patent application Attorney Docket No. D453:40289, entitled SYSTEM AND METHOD FOR CONTROLLING SYNCHRONIZATION OF A TIME-BASED PRESENTATION AND ITS ASSOCIATED ASSETS; Attorney Docket No. D453:40287, entitled SYSTEM AND METHOD FOR TRANSFORMING DATA INTO A TEMPLATE-BASED FORMAT; and Attorney Docket No. D453:39800, entitled SYSTEM AND METHOD FOR MANIPULATION AND INTERACTION OF TIME-BASED MIXED MEDIA FORMATS, all filed on August 31, 2000, the contents each being hereby expressly incorporated by reference.

**FIELD OF THE INVENTION**

The present invention relates to a system and method for collecting and assembling data for subsequent presentation to a recipient. More particularly, the invention relates to a system and method that provides an improved interface to facilitate the creation of such a presentation.

**BACKGROUND OF THE INVENTION**

Information is collected and presented to people in many different ways. Written text, in the form of books, newspapers, and magazines, represents one conventional way of presenting readers with information. Electronically, the written text, in the form of text data, may be presented to people over a computer or

5 other similar device. For example, people may access a web site that provides news and other textual information, along with information in other media formats, such as pictures and other images.

10 Another way in which information is presented to people is via a presentation, in which a person communicates such information to a person or group of persons. To assist the presenter in communicating such information, conventionally an overhead projector is used to display a sequence of transparent slides, with each slide typically consisting of text and/or some graphical image.

15 With computers gaining in terms of popularity, such presentations are often carried out through the use of a computer running appropriate software. One example of such software is PowerPoint™ available from Microsoft Corporation. As is well known in the art, PowerPoint™ creates a series of screen slides that typically include written text, and that may include a graphical image or the like. The screens are arranged in some order as dictated by the author. During presentation, the screens are displayed, with the progression from one screen to another being controlled by the presenter, or alternatively being performed automatically by the software.

25 While such software provides significant benefits and advantages, there are still disadvantages associated therewith. For example, in a conventional presentation, the author must bring the presentation, run PowerPoint™, and carry out the presentation. In addition, there is no provision for on-demand sharing of the presentation.

30 Moreover, a drawback associated with a number of the prior art systems is that the presentation becomes relatively large, and

5 includes a large number of discrete files. Such a presentation can  
become a burden to transfer. In addition, when those files are  
transferred and stored on a recipient's machine, they often consume  
a large amount of space, even after the recipient is finished with  
the presentation. Further, in a number of prior art systems the  
10 discrete files are transferred in an uncompressed format, which  
increases the burden of transferring the presentation.

15 Thus, it would be desirable to have a system and method that  
process the files comprising a presentation in such a manner so as  
to create a single file of relatively small size for transferring  
to a recipient. In addition, it would be desirable to have a  
system and method that is operative to remove the presentation from  
a recipient's machine after they view the presentation. Moreover,  
it would be desirable to process such a file at the recipient's  
machine. The present invention addresses one or more of these  
20 desirable features.

#### SUMMARY OF THE INVENTION

25 The present invention provides a system and method for  
creating a multi-media presentation, as well as allowing a  
recipient of the presentation to search through the presentation to  
retrieve and display desired subject matter. The invention  
preferably provides software that allows an author to record audio  
clips (e.g., narration) for one or more of the screens of the  
presentation, in any order, and in various manners. In addition,  
30 the invention maintains an internal, searchable data file with  
associated timing information to allow a recipient to find desired  
subject matter within the presentation, and to display the  
corresponding screen(s). Moreover, the invention transforms the  
plurality of files that comprise the presentation into an

5 executable file that can be viewed with a conventional web browser.

Thus, in one embodiment, the invention is directed to a method of preparing a mixed media presentation. Initially, plural sets of text data are received for insertion into respective screen slides. Audio data for one or more of the screen slides is also received. 10 The text data and associated timing information are copied into a data file, and the text and audio data are then concatenated together and then compressed. Finally, the screen slides are converted to images, and the images and concatenated audio and text data are assembled into an executable file, along with additional 15 controlling software.

In another embodiment, the invention is directed to a method of unpackaging and launching an executable file, including providing the executable file including executable code and a plurality of blocks of data, running the executable code to 20 identify one of the blocks, processing identification information in the block to determine the contents of the block, reading the data in the block and creating a corresponding directory if the block is a destination directory block, decompressing the data in the block and writing the decompressed data to an appropriate 25 directory if the block is a compressed file block, writing the data in the block to a temporary directory if the block contains a clean-up program, and saving the information in the block if the information contains auto-start path information.

### 30 DESCRIPTION OF THE DRAWINGS

Other features and advantages of the invention will become apparent from a description of the figures, in which:

FIG. 1 is a schematic diagram of a system for creating multi-media presentations according to one illustrative embodiment of the

5 present invention;

FIG. 2 is a flow chart depicting the operational flow of the system of FIG. 1 during the creation of a presentation;

10 FIG. 3 is a flow chart depicting in detail the exportation of data into a template-based format according to one illustrative embodiment of the invention;

FIG. 4 is a flow chart depicting in detail the assembly of a presentation into a single, executable file according to one illustrative embodiment of the invention;

15 FIG. 5 is a flow chart depicting the operational flow of an unpackaging process according to one illustrative embodiment of the invention;

FIG. 6 is a flow chart depicting the operational flow during playback of a presentation created according to the system of FIG. 1;

20 FIG. 7 is a flow chart of an event handling process according to one illustrative embodiment of the invention; and

FIGS. 8 through 13 are screen shots during creation of a multi-media presentation.

25 DETAILED DESCRIPTION OF THE INVENTION

Referring now to FIGS. 1 and 2, there is shown a system 20 for creating multi-media presentations according to one illustrative embodiment of the present invention. System 20 includes a user interface 22 including an input device 23 and display 28, a processor 24, memory 26, and microphone 30. Memory 26 stores suitable software for creating the multi-media presentations, as is described in more detail below.

30 Input device 23 of user interface 22 may take any suitable form, such as a keyboard, keypad, mouse, any other input device, or

5 any combination thereof. An author may enter text data through user interface 22, or may use the interface to select appropriate graphical information from a disk storage medium or other source, as is described in more detail below.

10 Processor 24 is connected to user interface 22, and to memory 26. Processor retrieves the presentation-creating software from memory, receives data and control commands from user interface 22, and displays the presentation information on display 28.

15 The present invention can be configured to be used, independently, by an end-user or, in the alternative, the invention can be integrated, as an add-in, into another presentation development application. In a preferred embodiment, the system of the present invention is designed for use in conjunction with Microsoft PowerPoint™. It will be understood by those skilled in the art that PowerPoint™ is merely one suitable software program  
20 into which the present invention may be incorporated.

25 Referring now to FIG. 2, an illustrative method according to the invention will be described for modifying and preparing an existing presentation that consists of multiple digital assets in the form of screen slides. Operation begins at step 40, with the processor 24 retrieving the presentation-creating software from memory 26. At step 42, processor initializes the system 20. Preferably, initialization consists of setting microphone 30 as the currently selected recording object and setting the recording level to one that will result in the recording being at a desirable  
30 level, such as 50%.

During initialization, processor 24 also preferably resets the size of link sound files. Preferably, processor 24 is programmed to initialize the linked sound files to a relatively large size. In a preferred embodiment, the preset size is 2 megabytes. It will

5 be understood that the file size could be made to be larger or smaller, as necessary.

At step 44, system 20 receives an existing presentation, either from an external source, or from memory 26. The presentation consists of a plurality of screen slides arranged in some predetermined order. In one embodiment, the first screen slide of the presentation is presented on display 28. At step 46, the author selects one of the screen slides, for example, by clicking on suitable icons in a tool bar to scroll through the screen slides, through a drop-down menu, or in any other suitable manner.

Once the author has selected a particular screen slide, operation proceeds to step 48, and processor 24 receives an audio clip to be linked with that screen slide. A suitable icon is preferably displayed on the screen to alert the author that they can begin speaking the desired audio clip, with the microphone 30 capturing the audio and forwarding the audio data on to processor 24. Alternatively, the audio clip can be imported from a file, disk, or the like.

Processor 24 stores the audio data in a suitable temporary file. In addition, processor 24 generates a link between the audio data and the corresponding screen slide, and stores that link, either with the audio clip itself, or in a separate linked file. Alternatively, the audio clip can be stored directly with the screen slide in a slide object, as described in more detail below, thereby obviating the need for any file linking.

In another embodiment, the author can progress through all of the slides sequentially, such as if they were making a live presentation, without the need to use the narration capture interface. The narration would be captured automatically along

5 with the slide advance timings. This embodiment is very useful for creating an archive of a live presentation at the time of the live presentation and as a by-product of the live presentation.

10 At query block 50, processor 24 determines whether there are additional slides for which an author desires to record audio clips. In one illustrative embodiment, processor may query the author whether they wish to record additional audio clips. If so, operator proceeds back to step 46, and the author selects another slide. Alternatively, processor 24 can display the screen slides sequentially, with the author deciding whether to record an audio clip for a particular screen slide when that screen slide is displayed on display 28.

15 If, on the other hand, there are no more audio clips to be recorded, then operation proceeds to step 52, and the author selects one or more of the screen slides for assembling into a final presentation, along with a desired compression format to be employed. Such selection of the slides can be done through a drop-down menu, or by scrolling through the various screen slides and selecting the desired slides, or in any other suitable manner. The selection of the compression format can be done via a drop-down or other suitable menu.

20 Once the author has finished selecting the slides for assembly, operation proceeds to step 54, and processor 24 generates a playlist object corresponding to the selected slides. The playlist object is an intermediate representation of the metadata, and contains the semantic and relationship information for the content, and is a self-contained entity that consists of both data and procedures to manipulate the data. The playlist object includes a media object to store the audio clips, a screen slide object to store the screen images, and a text object to store the



5 text contained in the various screen slides. The media, text, and screen objects also store timing information that defines the temporal relationships between the respective types of data, as is described in more detail below.

10 Then, at step 56, processor 24 copies the text from the selected screen slides as searchable text data into the text object. The text for each slide may be preceded by an appropriate header or the like so that a link is maintained between the text data and the particular screen slide from which that text data originated. At step 58, the individual audio files from each of  
15 the selected screen slides are extracted from the respective slide objects and are concatenated into a single audio file which is stored in the media object. The single audio file is then compressed using the particular compression format previously selected by the author, at step 60. Thus, by allowing the author  
20 to select the compression format and then compressing the audio file after concatenating the individual audio clips together, the author may to some extent control the file size and sound quality.

25 Alternatively, instead of "physically" concatenating the audio files together as described above, a new file may be created that maintains plural links to the respective audio files. This is an alternate version of concatenation that may be used in connection with the invention.

30 At step 62, slide timing information from the selected slides is extracted from each slide object, and the information is stored in a suitable file. For example, each screen slide will have timing information relating to the start and stop times that the screen slide is to be displayed, which serves to determine the order in which the screen slides are to be displayed.

5           Then, at step 64, the selected screen slides are saved in a graphics file format, preferably in Graphics Interchange Format ("GIF") format, and stored in the screen slide object. It will be apparent to those skilled in the art that other suitable graphics file formats may also be used.

10           At step 66, processor 24 assembles the selected screen slides, in GIF or some other format, with the corresponding audio files, text file, and the file containing the timing information, to create a single compressed, executable file. The process of forming the single executable file is described in greater detail  
15 below in connection with FIG. 4. The executable file may then be forwarded to one or more recipients for subsequent viewing of the presentation. For example, the file can be a Windows® 98 or Windows® NT standard executable file, as is well known to those skilled in the art. As is well known, an executable file is a  
20 binary file containing a program in machine language that is ready to be executed when the file is selected. In that manner, the executable file may be opened within a suitable web browser or directly in the operating system interface without the need for the presentation software that was used to create the presentation, as  
25 is described in greater detail below in connection with FIG. 3.

          It will be apparent that the system 20 may be used with appropriate software to create the entire presentation at one time. Thus, rather than retrieving a multi-media presentation, system 20 can present an author with blank templates, into which the desired  
30 text and/or graphical data can be entered. Audio clips can then be recorded for one or more of the created slides, either concurrently with the creation of the slide, or after the slides are completed.

5 Referring to FIG. 3, an export process that is used to process  
data contained in the playlist object is described in detail. The  
export process is designed to transform the data into a template-  
defined data format suitable for display within a browser. The  
export process utilizes a plurality of text templates and slide  
10 page templates to arrange the meta data from the playlist object  
such that it is in a browser-suitable format, so that the  
presentation can be displayed in a browser without the need for the  
presentation software used to create the presentation. In  
addition, executable java scripts and applets are generated and  
15 inserted into the template, and are run in the browser to allow for  
the presentation to be displayed in the browser.

The export process begins at step 70, with processor 24  
retrieving the playlist object with the slides and clips in  
temporal order. At step 72, the export process retrieves a  
20 template from the set of templates. For example, the template may  
be a text information file that will contain information describing  
how the meta data from the playlist object needs to be formatted  
into a format that is suitable for running in the browser. In  
addition, the template contains information relating to the layout  
25 of the presentation, for example, the relative locations on the  
display of the slides, table of contents, media player controls,  
search results, and the like. The template also will contain  
formatting information, for example, text font, size, color, and  
similar attributes. Moreover, the template also contains  
30 references to other files that are used in the display of the  
presentation.

At step 74, the export process processes the command  
parameters contained in the template to determine what type of file

5 it is, and the destination of the completed file. At step 76, the  
export process reads the first tag in the template. The tag serves  
as a text replacement holder. For example, the first tag may  
instruct the export process to process the table of contents  
information, the text information, or the slide page information.  
10 Within the first tag there are a number of subordinate tags (i.e.,  
there is a hierarchy of inner and outer loops of tags). Thus,  
where the first tag corresponds to the table of contents, there  
will be multiple entries to be processed, such as the title of each  
slide. Then, for the first title, there are plural tags in the  
15 template to be replaced with corresponding data from the playlist  
object. For example, the tags may correspond to character font,  
size, spacing, positioning, and the like. Thus, each tag is  
replaced by the corresponding information contained in the playlist  
object. In the case where the template is a text template,  
20 processor 24 retrieves the text-related meta data and inserts that  
information into the template. Likewise, in the case of a slide  
page template, the corresponding meta data relating to the slide is  
retrieved and inserted into the appropriate location of the  
template based on the tags in the template.  
25 Thus, at step 78, based on the particular tag read by the  
export process, corresponding meta data is retrieved from the  
playlist object and inserted into the template, along with  
references to the appropriate files, for example, a slide file or  
the data file containing the actual text data. At query block 80,  
30 the export process determines whether there are additional tags  
remaining in the template to be replaced with information from the  
playlist object. If so, operation proceeds back to step 76.

5           On the other hand, if all of the tags have been replaced for  
a particular template, operation instead proceeds to query block  
82, and the export process determines whether there are additional  
templates to be processed. If so, operation proceeds back to step  
72. If not, operation proceeds to step 84, and the export process  
10 searches for .tpl files (i.e., template files). For each .tpl  
file, the export process creates a new file for each slide and  
replaces an internal tag with the name of the graphic file. The  
process then terminates.

15           Thus, by processing the data using the export process and the  
template-defined format, the presentation may be viewed in a  
conventional web browser. Thus, a recipient of the presentation  
need not have PowerPoint™ software in order to view the  
presentation.

20           Referring now to FIG. 4, the process of packaging the files  
into a single, executable file is described in detail. Operation  
begins at step 90, with processor 24 receiving input from the  
author regarding packaging information and preferences. For  
example, the author is prompted to input an output file name, the  
name of the directory to be packaged (i.e., where the respective  
25 files are currently stored), a directory name where the unpackaged  
files should be stored, an auto-start file (i.e., the first file to  
be opened when the executable file is selected), and package  
identification information to uniquely identify the package and its  
source or origin. At step 92, processor 24 creates and opens an  
30 output file into which the single file will be stored.

          At step 94, executable code is copied to the output file. As  
is well known in the art, the executable code is the code that is  
run when an executable file is selected. The executable code

5 controls the unpackaging process, as is described in more detail below in connection with FIG. 5.

10 At step 96, in the event that package identification information was input by the author, corresponding block identification information and package identification information is written to the output file. The information preferably consists of a starting block flag, block identification information, and the package identification information itself.

15 Operation then proceeds to step 98, and the destination directory information is stored in the output file, along with a starting block flag and block identification information to identify the contents of the block. Following the identification information, a data string (e.g., a 16-bit string) is written to the output file, which indicates the length of the directory information. And finally, the destination directory information  
20 itself is written to the output file.

25 Then, at step 100, each file in the directory to be packaged is sequentially processed and written to the output file as an individual block. As described above, an author will have previously selected a number of the screen slides to be included in the presentation. Processor 24 accesses the playlist object and retrieves the GIF files for the selected slides from the screen slide object, the single concatenated and compressed audio file from the media object, and the data file containing the corresponding text data from the text object. In addition,  
30 processor 24 retrieves the file containing the timing information for the selected slides.

At step 100, for each file a starting block flag is written to the output file. File identification information is then stored to

5 identify the file. Next, the string length of the file name is written to the output file, followed by the file name itself. Then, processor 24 determines whether the file is compressed: if not, the file is compressed and stored in a temporary location. Processor 24 next writes information (preferably 32 bits) relating  
10 to the size of the compressed file to the output file. Finally, the compressed file is written to the output file, either from the temporary location, or from the originating directory. If a temporary file was created, it is then deleted.

15 Operation then proceeds to query block 102, and processor 24 determines whether the unpackaging directory is a temporary file. If not, operation proceeds to query block 106. If so, operation instead proceeds to step 104, and a clean-up program is retrieved by processor 24 to be included in the output file. The clean-up program is an executable file upon being expanded, and is operative  
20 to delete the files contained in a particular temporary file. In this manner, the expanded files contained within the executable file do not permanently occupy memory on the recipient's machine, unless the presentation is intended to be permanently saved on the recipient's machine, in which case a destination directory other  
25 than the temporary directory is selected.

Storage of the clean-up program is as follows: first, a starting block flag and clean-up program identification information are written to the output file. Then, the clean-up program is compressed to a temporary location in memory. The length of the  
30 compressed program is written to the output file, followed by the copy of the compressed program. The temporary compressed file is then deleted, and operation proceeds to query block 106.

5           At query block 106, processor 24 determines whether one of the  
files in the bundle was designated as an auto-start file. If not,  
operation terminates at step 110 with the closing of the output  
file. On the other hand, if one of the files was designated as an  
10       auto-start file, then operation instead proceeds to step 108, and  
starting block flag and auto-start identification information is  
written to the output file, followed by a 16-bit string to indicate  
the length of the auto-start string name, which is followed by the  
auto-start string itself. Operation then terminates at step 110,  
and the output file is closed.

15           In an alternative embodiment, the package process inserts a  
source-identifying block into the package, with such block serving  
to identify the source of the package. In this manner, the  
unpackaging process described below can verify the source of the  
package to ensure that the package does not contain any potentially  
20       harmful or offensive data.

          Referring now to FIG. 5, the unpackaging of the packaged  
presentation is described in more detail. As is described above,  
a presentation is packaged into a single, executable file. The  
executable file may then be transferred to one or more recipients  
25       in various ways, either as an email attachment over a  
communications network, on a disk, or in any other suitable manner.

          In another embodiment, the executable file is transferred to  
a host web site, where the file is unpackaged as described below  
and made available to recipients over the Internet or some other  
30       communication network. In that situation, the recipient need not  
unpack the presentation on their desktop; rather, the unpackaged  
presentation may be streamed to the recipient slide-by-slide on an  
on-demand basis.



5 In the case where the executable file is delivered directly to  
the recipient, operation begins at step 120, with the recipient  
selecting the executable file, for example, by double clicking on  
an appropriate icon on the recipient's display. Once the recipient  
selects the executable file, operation proceeds to step 122, and  
10 the executable code in the file automatically runs and scans the  
data in the output file until it encounters the first starting  
block flag. Next, the executable code determines the identity of  
the data contained in the first block, by reviewing the  
identification information stored in the block during the packaging  
15 process.

At query block 124, if the block is determined to be the  
package identification block, then operation proceeds directly to  
query block 146 to scan the data for the next block in the file.  
The package identification block is not processed by the executable  
20 code during the unpackaging process. If the block is determined to  
not be the package identification block, then operation proceeds to  
query block 126, and the executable code determines whether the  
block contains unpackaging directory information. If so, then  
operation proceeds to step 128, and the executable code reads the  
25 information contained in the block to determine the full path name  
of the output directory and subdirectories in which to store the  
files expanded during the unpackaging process. The code then  
creates all of the necessary directories and subdirectories into  
which the expanded files will be stored. Operation then proceeds  
30 to query block 130, and the executable code determines whether the  
directory into which the files will be saved is a temporary  
directory. If not, operation proceeds to query block 146. If in  
fact the directory is a temporary directory, then operation

5 proceeds to step 132, and a registry entry is created to control the clean-up program to be executed the next time the recipient logs in to their machine. Operation then proceeds to query block 146.

10 If at query block 126 the data block is determined to not be a directory information block, then operation proceeds to query block 134, and the executable code determines whether the block is a compressed file block. If it is, then operation proceeds to step 136, and the file name for that file is read from the block and concatenated with the destination directory. The executable code  
15 then determines whether a corresponding subdirectory exists and, if not, the subdirectory is created and opened. The length of the compressed file is determined, and if the data needs to be decompressed, it is decompressed and written to the destination directory. Operation then proceeds to query block 146.

20 If at query block 134 the block is determined to not be a compressed file, then at query block 138 the code determines whether the block contains the clean-up program. If so, operation proceeds to query block 140, and it is then determined whether the clean-up program is needed or not, by checking the machine's  
25 temporary directory to determine whether a copy of the program is already resident on the machine. If so, operation proceeds to query block 146. On the other hand, if there is no resident copy of the program, operation instead proceeds to step 142, and the clean-up program is decompressed to an executable file in a  
30 temporary directory, such as the Windows temporary directory. Operation then proceeds to query block 146.

If the block does not contain the clean-up program, then operation proceeds to step 144, and the executable code determines

5 that the block contains the auto-start file information, and the code saves the path information of the auto-start file for future use. Operation then proceeds to query block 146.

10 At query block 146, the executable code determines whether there are additional blocks to be unpackaged. If so, the code reads the identification information of the next block at step 148, and operation then proceeds back to query block 124 to determine the block type.

15 If at query block 146 it is determined that there are no more blocks to be unpackaged, then operation proceeds to query block 150, and the code determines whether there is a file designated as the auto-start file, by checking for auto-start path information. If there is an auto-start file, then operation proceeds to step 152, and the corresponding file is opened to begin the presentation.

20 Where the packaged presentation is transferred to an ASP host, the host is programmed to override the auto-start data and the destination directory information. The host preferably includes codes that investigate the package identification information to ensure that the executable file was generated by a known, trusted source, and not by some unknown entity that might be transmitting a virus or other undesirable content. Once the identity of the author is verified, the package is then unpackaged to a destination directory as determined by the host, and the host stores the presentation until a user accesses the host and requests the presentation. The host can then stream the presentation to the user in any suitable, well known manner as described above.

Referring now to FIG. 6, playback of the created presentation is described in more detail. Initially, the presentation is

5 obtained by an intended recipient, either on a disk or other  
storage medium, as an email attachment, or transferred over a  
computer network, such as over the Internet. Then, at step 200,  
the recipient opens the file by clicking on a suitable icon  
representing the presentation, or in any other well-known manner.  
10 As described above, when the bundle is extracted by the recipient  
opening the self-executing file, one of the sub-files is designated  
as the initial file to be opened, as in conventional in self-  
executing files. In addition, the extracted files are written to  
the appropriate destinations for subsequent retrieval during the  
15 presentation.

At step 202, the presentation is displayed to the recipient,  
with the slides being sequentially displayed along with any  
corresponding audio clips for the respective slides. In addition,  
a table of contents is displayed on the display, and includes the  
20 title of each slide in the presentation (FIG. 13). The titles may  
be selected by the recipient to advance the presentation to the  
corresponding slide. At query block 204, the recipient's machine  
(hereinafter "the machine") determines whether the recipient has  
requested a search for a particular text string within the  
25 presentation. In one embodiment, such a request is made by  
entering the text string in an appropriate box on the screen and  
then clicking on a corresponding button on the screen (see FIG.  
13). If the recipient does not request a search for text, then  
operation proceeds to query block 205, and the machine determines  
30 whether the recipient has made a selection of one of the slide  
titles in the table of contents. If so, the presentation is  
advanced to the selected slide, and that slide is displayed along  
with the corresponding portion of the concatenated audio file, at

5 step 206. A time-based index into the concatenated audio file is provided, and instructions are transmitted to reposition an audio player to the appropriate point in the audio file based on the time-based relationship between the slide and the audio file. Operation then proceeds back to query block 204. If the recipient  
10 does not select any of the titles in the table of contents, then operation instead proceeds to step 207, and the presentation continues to completion, and operation then terminates.

15 If, on the other hand, the recipient makes a request for a text search, operation proceeds to step 208, and the recipient enters their text string, which is received by system 20. At step 209, the machine accesses the meta data file that was included in the self-executing file and that contains all of the meta data information necessary for playback, including the text that appears on the individual slides. At step 210, the machine compares the  
20 text string with the text contained in the data file. At query block 212, the machine determines whether a match exists. If not, then at step 214 the recipient is notified that there is no match for the entered text string. Operation then proceeds back to step 204, and the recipient may enter another text string to be  
25 searched.

If there is a match between the text string and the text in the data file, operation proceeds to step 216, and the machine retrieves the appropriate GIF file and determines the corresponding position within the single audio file and presents the screen slide  
30 and corresponding portion of the audio file to the recipient. There are many well-known ways in which system may determine the appropriate GIF file to retrieve. For example, an association

5 table may be maintained to link the text of each slide with a corresponding GIF file.

It will be apparent that a recipient may request that a search be conducted before the presentation begins, during the presentation, or after the presentation is completed.

10 Once the slide and corresponding portion of the audio file are presented to the recipient, the presentation may be continued, sequentially from the selected slide to the end of the presentation, operation may terminate, or operation may proceed back to query block 204 to allow the recipient to search for another text string.

15 Referring to FIG. 7, the operational flow of event handling software included in one illustrative embodiment of the invention is shown in detail. The event handling software controls the navigation through a presentation at the recipient's machine. The software relies on a set of event data that contains all of the information relating to the timing of the presentation. For example, the event data includes information concerning the start and stop times of each slide page, of each of the clips in a clip list, and of each audio clip. In addition, the event data may include information concerning when the presentation should automatically pause or skip to a new position.

20 Operation of the event handling software begins at step 220, and the presentation begins, for example, when the self-executing file is opened. The presentation then begins to be displayed, for example, at the beginning of the presentation. At step 222, the recipient's machine is controlled by the event handling software to determine the time of the current position of the presentation. For example, when the presentation is launched from the beginning,

5 the software determines that the time is either at time zero or  
only a few milliseconds. At step 224, the time is compared with  
the event data for the respective slides, and the slide whose time  
is either equal to or less than the determined time is selected and  
displayed in the slide window on the recipient's machine, at step  
10 226.

At step 228, the event handler software calculates a timeout  
based on the current time of the presentation and the stop time of  
the slide being displayed. At step 230, the event handler sets a  
clock to fire an event trigger upon reaching the timeout.

15 At query block 232, the event handler determines whether the  
event trigger has fired. If so, then operation proceeds to step  
234, and the event trigger initiates a polling process to  
repeatedly (e.g., every 200 milliseconds) determine the current  
position of the presentation. At step 236, the current position is  
20 compared with the event data for the respective slides. At step  
238, the slide whose time is 1) equal to or 2) less than, and  
closest in time to, the current time is selected and the slide  
window is updated with the selected slide. At step 240, the event  
handler calculates a timeout based on the current time and the stop  
25 time of the slide, and resets the clock to fire an event trigger  
upon reaching the new timeout. Operation then proceeds back to  
query block 232.

On the other hand, if at query block 232 it is determined that  
the event trigger has not yet fired, operation instead proceeds to  
30 query block 242, and the event handler determines whether the  
presentation has been either paused or stopped by the recipient,  
for example, by clicking on a pause or stop button, or by selecting  
another slide for presentation. If not, operation loops back to

5 query block 232. If the presentation has been paused or stopped,  
then operation proceeds to step 244, and the presentation is  
stopped. Also, the event trigger clock is cleared. Operation then  
proceeds to query block 246, and the event handler determines  
whether the presentation has been restarted, for example, by the  
10 recipient pressing a start button, or repressing the pause button.  
If the presentation has been restarted, operation proceeds back to  
step 222 to determine the time of the new position of the  
presentation.

15 It will be understood that when the recipient selects a new  
slide for display, the presentation is automatically restarted at  
step 246, and operation then proceeds back to step 222.

20 The above description of the event handler deals primarily  
with the screen slides themselves. However, it will be apparent to  
those skilled in the art that the event handler would perform the  
same functions for synchronizing the display of textual  
information, audio clips, and the like.

25 Referring now to FIGS. 8 through 13, there is shown one  
illustrative embodiment of various interface screens generated by  
system 20 to facilitate creation of a multi-media presentation by  
an author. As shown in FIG. 8, system 20 preferably displays each  
of the generated screen slides 21 with the accompanying text for  
each. In addition, a user interface window 320 is provided to  
guide an author through the process of creating a multi-media  
presentation. The user interface navigates the author through the  
30 steps of initializing the system 20, recording narration for the  
respective slides 21, previewing a presentation, and packaging the  
final presentation. The user interface 320 includes a Cancel  
button 322, a Back button 324, a Next button 326, and a Finish



5 button 328 to allow the author to control navigation through the process.

10 FIG. 9 shows a user interface 330 which may be used by an author to calibrate the microphone. The calibration of the microphone is performed by providing a volume control 332 that can be manipulated by the author to adjust the volume of the microphone. The range of control spans from 0 to 100%. The screen preferably displays the control level at which the microphone is set in a display window 334. The level can be increased and decreased by manipulating a slide bar 335. To test the volume level to determine whether it is acceptable, a control panel 336 is provided that enables the author to record and then play back a test clip to determine if the volume level of the microphone is acceptable. Control panel 336 preferably has a record button 338, play button 340 and stop button 342. To test the microphone, the author clicks the record button 338 and speaks into the microphone. When the author is finished recording, the stop button 342 is pressed. The author can listen to the recording by clicking the play button 340. When the volume level has been set to a desirable level, the author can click the NEXT button 326 to continue with the creation of a presentation. If, at any time, the author wants to return to a previous window to change a setting, the author can do so by clicking the BACK button 324.

30 FIG. 10 illustrates a user interface 350 that assists the author in narrating a slide. To begin recording on a particular slide, RECORD button 352 is clicked. The author can stop the recording at anytime by clicking on STOP button 354. The author can also pause the recording by pressing PAUSE button 356. The author can play back the recording by clicking on PLAY button 358

5 to ensure that the audio clip is audible and clear. If the content  
is not as desired, the author can override the previous audio clip  
by recording over it. In addition, interface 350 includes Previous  
and Next Slide Buttons 357 and 359, which allow the author to  
navigate through the respective slides 21. Thus, the present  
10 system allows the author to record the slides out of order, giving  
the author greater independence in working on the slides in the  
order desired by the author and, not necessarily, in the order that  
the slides appear in the presentation material.

15 When finished narrating a slide, the author can proceed to the  
next slide by clicking on NEXT slide button 359, or to a previous  
slide by clicking on PREVIOUS slide button 357. The activation of  
either of those buttons will automatically terminate the narration  
for that slide. Thus, it will be apparent that user interface 350  
allows the author to record narration for the respective slides in  
20 any order. The audio for each slide is independent of the other  
slides, and thus, the audio for the slides can be recorded in an  
order independent of the order of the slides.

25 The interface 350 preferably includes a slide time meter 364  
that displays the length of the audio for each slide and a total  
time meter 366 that displays the length of the audio for the entire  
presentation. This allows the author to keep track of the length  
of the entire presentation as the author is recording the audio for  
each slide.

30 In addition to providing information regarding the length of  
the audio recordings on interface 350, the length of the various  
audio recordings are also provided as time meter displays 367 under  
each slide. This enables the author to view the audio recording  
length for all of the slides simultaneously.

5           In one embodiment, system 20 requires that narration be  
recorded for each slide, with the length of the recording  
determining the length of time for which the slide will be  
displayed. Alternatively, if narration is not recorded for a  
particular slide or slides, a default display time may be assigned  
10 to that slide, such as 4 seconds or some other amount of time. Or,  
system 20 may query the author to enter a default time for a  
particular slide for which no narration has been recorded.

FIG. 11 shows a user interface 360 that allows an author to  
preview and/or package a finished presentation. Interface 360  
15 includes a Preview button 362, which if clicked causes system 20 to  
launch the presentation immediately, so as to allow the author to  
preview the presentation before completion. The presentation  
material can be packaged so as to be optimized for sound quality or  
optimized for size. The author makes their selection by clicking  
20 on one of two windows 365 and 367. Clicking on the preview button  
causes the processor 24 to carry out the concatenating,  
compressing, and export processes so as to have the data in a  
format suitable for presentation within the web browser. In  
addition, the preview function causes the processor to launch the  
25 auto-start file in the web browser automatically, as would be done  
by the unpackaging process described above.

FIG. 12 depicts a user interface 370 to allow the author to  
select a file name under which the presentation will be stored. In  
a preferred embodiment, optimizing the presentation for size  
30 provides a compression of about 6500 bits per second, whereas  
optimizing for sound quality provides a compression of about 8500  
bits per second. In the embodiment shown in FIGS. 9 and 10, the  
user interfaces 360 and 370 only allow the author two choices for

5 optimization, namely, optimization for sound quality and  
optimization for size. The system, however, can be adapted to  
provide additional optimization choices to the author. For  
instance, if authors desire a different level of audio, e.g., audio  
at a high bandwidth to facilitate high quality CD recording, the  
10 system can be adapted to provide additional optimization choices to  
the author. The optimization for sound quality and size are  
preferable for presentation materials that mainly contain audio  
consisting of the spoken word. In the case of audio containing  
spoken word, the frequency response is small and telephone-like,  
15 monaural quality is the audio level that is required to be provided  
by the system.

User interface 370 assists the author in saving the  
presentation material. In one illustrative embodiment, system 20  
keeps track of the last used directory 374 and displays the  
directory name in the "save file as" window 372. That directory is  
concatenated with the current name 376 of the presentation material  
to create the file name for the presentation. For instance, user  
interface 370 displays a directory of "D:\MyDocuments\" and a file  
name of "testing of hotfoot.exe." The presentation material is  
25 thus saved in the specified directory under the specified file  
name. User interface also includes a Browse button 378 to allow an  
author to select another path in which to store the presentation.  
In yet another embodiment, system 20 inserts a default directory  
into window 372, rather than the last-used directory.

30 As is described above, the creation of the playlist object  
allows the system of the present invention to be compatible with  
numerous other applications because the playlist object simplifies,  
generalizes, and abstracts the process of data storage, post-

5 processing, and transmission. Thus, the playlist can be reused in  
other applications, while the playlist ensures the referential  
integrity, provides object modeling, provides consistency between  
what is done in the present system with other applications, which  
allows efficient and compatible data sharing between different  
10 applications.

The system loops through each slide, extracts the text of the  
slide, and removes the megaphone object from each slide and exports  
it as a .gif file. The exportation of the slide object as a .gif  
file can be done by using Microsoft PowerPoint™. Auto-numbering  
15 is automatically turned off by the system so as not to get a "1" at  
the bottom of each page. The duration of the audio file for each  
file is measured and, if the slide has no audio duration, a  
duration of four seconds is assigned. The reason for assigning a  
four second duration is that the recipient's application is  
20 responsible for advancing the slides. If there is no audio  
recorded for the slide, the slide will be shown for four seconds  
and then is automatically advanced to the next slide.

The corresponding audio clips for the selected slides are also  
retrieved and saved as .wav files. The .wav files are concatenated  
25 and integrated together. The .wav files can also be converted to  
other digital media continuous stream formats, such as MP3. It  
will be apparent to those skilled in the art that by concatenating  
the files together, prior to encoding into another digital sound  
format, the notion of independent audio linked to slides is  
30 transformed into a coherent and unchangeable presentation format.  
The coherent format allows the recipient to jump from slide to  
slide randomly and out of order but does not allow the recipient to

5 modify or change the audio or the slides. Therefore, the intention of the publisher is preserved.

10 In one illustrative embodiment, the .wav file is converted to a Windows Media file and the bit rate is set to the bit rate previously determined by choosing optimization for size or sound quality. The Windows Media file is a single media file that can be attached to the playlist object.

15 The author has the option of choosing which slides will be included in the presentation package, with such selections being done in any suitable manner, such as by clicking on a window next to each slide, through a drop-down menu, or in any other suitable manner. For instance, the author can chose slides 1, 3 and 7 and those become packaged in the presentation. Or the author can unselect 3 and select another slide, for instance slide 8. The fact that the audio is tied to a slide, as opposed to across the entire presentation, allows the author to chose the order and the slides to be included in the presentation. System 20 extracts the necessary information from the selected slides only when packaging the presentation.

25 The packaged presentation is then subjected to the above-described export process, in which the necessary information is extracted from the playlist object and put into a template-defined format suitable for display within a browser. In one embodiment, system 20 stores the title of each slide in a suitable file for creating the table of contents, and strips all of the text from each slide and stores the text in another file, as is described above. The information proceeds to the packaging process which, as described in detail above, takes the files and subdirectories,

5 including the media file and the slides, and creates an executable file.

10 The packaging process gathers a relatively large number of files, for example as many as 30 to 40 individual files, that are created by system 20 when a slide presentation is created. There may also be other files, such as external files, that also need to be included in a presentation. The packaging process gathers the external files along with the presentation files and creates a single, simplified package. In a preferred embodiment, the packaging and unpackaging functions are completed without  
15 interfacing with the author. One of the files in the package is designated as the file to be opened when the package is extracted. A marker is also placed in the executable file that identifies the file as one that is compatible with the application of the present system.

20 Referring now to FIG. 13, there is shown a portion of the presentation, for example when an author has selected the Preview option. The presentation includes a table of contents 400 that includes the title for each of the slides. Each title may be clicked on to immediately display the corresponding slide. In  
25 addition, the presentation displays one of the slides 21. Moreover, the presentation includes a window 402 into which the recipient may enter a text string to be searched for. A Search button 404 is provided and may be selected by the recipient to begin a search for text, as is described above in more detail. The  
30 search results are displayed in a portion of the screen 406. In one embodiment, if there is a match, the slide that contains the matched text is automatically retrieved and displayed, along with the corresponding audio clip. Alternatively, the results may be

5 displayed for the recipient, with the recipient then selecting one of the slides for display. The display preferably also includes a Play button 408, Pause button 410, and running indicator bar 412 to indicate the current state of the presentation.

10 While the above description has focused primarily on a presentation consisting of screen slides and corresponding audio, it will be readily understood by those having ordinary skill in the art that the various aspects of the present invention have utility in connection with other data-presenting formats. For example, the present invention may be used to export, package, unpackage, and  
15 display presentations consisting of spread sheets and corresponding audio clips for one or more of the respective cells in the spread sheet, word processing documents with corresponding audio clips for the various pages of the document, charts, screen capture scenarios, and the like. It will be understood that the various  
20 aspects of the invention, including the packaging process, export process, unpackaging process, and event handling process, have utility in connection with various different types of information, and that the screen slide presentation described herein is but one illustrative embodiment of the utility of the invention. Thus, the  
25 export process, packaging process, unpackaging process, and event handling process can each be used in connection with various types of information.

By way of example, in the case of a spreadsheet, the present invention may be used to add audio clips (e.g., voice comments) to  
30 particular cells within the spreadsheet, in a similar manner to the audio clips being associated with the respective screen slides. The invention will concatenate the audio clips into a file, compress the file, and assemble the compressed file, spreadsheet



5 graphics file, and the other files described above into a single, executable file.

10 In addition, a word processing document can be associated with one or more audio clips, wherein the audio clips are linked to particular pages, chapters, paragraphs, and the like, of the document. The export process, packaging process, and unpackaging process are carried out in much the same way as in the case of the screen slide presentation.

15 As used herein, the term "digital asset" is defined as a collection of data that is presented to a viewer, such as a screen slide, a video clip, an audio clip, a spreadsheet, a word processing document, and the like.

20 As described above, in the case of a presentation consisting of plural screen slides, the text from each screen slide is preferably extracted and stored in a data file, with such data being available for searching during subsequent presentation. Where the invention is dealing with other types of digital assets, some other type of data may be extracted from the respective assets for use in intelligently navigating through the presentation. For example, in the case of a video signal, closed captioning information may be extracted from the video and stored in the data file. Alternatively, selected video frames may be extracted and stored, such as transitory frames or other important frames. Moreover, in the case of audio data, key words may be extracted from the audio and stored in the data file.

30 In addition, while the above description focuses primarily on audio clips being linked to respective digital assets (e.g., screen slides, video clips, and the like), the audio clips can be replaced with any continuous stream media format, such as video, audio and

5 video, animations, telemetry; and the like. Thus, the invention  
has utility with any continuous stream media format, and it will be  
understood by those skilled in the art that audio clips are but one  
example thereof.

10 From the foregoing, it will be apparent to those skilled in  
the art that the system and method of the present invention provide  
for creating a multi-media presentation in a user-friendly,  
efficient manner. The system also provides a presentation that can  
be searched to arrive at desired subject matter.

15 While the above description contains many specific features of  
the invention, these should not be construed as limitations on the  
scope of the invention, but rather as exemplary embodiments  
thereof. Many other variations are possible. Accordingly, the  
scope of the invention should be determined not by the embodiments  
illustrated, but by the appended claims and their legal  
20 equivalents.